MEAB

MSU LAB

- LABORATORY MIXER-SETTLER EQUIPMENT

Equipment ideally suited for: - Flow Sheet Evaluation

- Pilot Plant Operation and Small Scale Production

- Education and Industrial Training









The laboratory and pilot scale mixer-settler units are available in flow (org+aq+recycle) ranges from 50 to 500 l/h.

MEAB Metallextraktion AB, Datavägen 51, SE-43632 ASKIM,

***** +46 31 685414. Fax +46 31 685474.

www.meab-mx.se

MEAB ChemieTechnik GmbH, Dennewartstrasse 25, D-52068 AACHEN,

***** +49 241 9631180. www.meab-mx.com

Fax +49 241 9631185.

Germany

contact@meab-mx.se

Sweden

contact@meab-mx.com

MSU LAB MIXER-SETTLER UNITS

LABORATORY EQUIPMENT





The laboratory and pilot scale mixer-settler units are traditionally designed pump mixersettler units, with squared mixing chambers (mixers) and box-type settling compartments (settlers). The mixers are equipped with adjustable speed stirrers and the settlers with picket fences for the distribution of the dispersion over the whole cross-section of the settler. An adjustable jackleg for the outflow of the heavier solvent controls the phase boundary level at varying liquid densities. A heavier solvent recycle is integrated in the construction. Each unit is designed to operate hydrodynamically independent of other units, an advantage that enables all units to be placed horizontally, one after the other. This arrangement implies flexibility in the experimental set-up. Experience shows that the mixer-settler units are large enough to provide reliable chemical data and sufficient product solutions for further evaluation. At the same time, the units are small enough to minimise consumption of chemicals, maintenance, operator attendance and other related costs.

The MSU laboratory mixer-settler units have been produced in stainless steel (SS), polypropylene (PP), polyvinyl chloride (PVC) or polyvinylidene fluoride (PVDF) according to customer's demand. The units are commonly used for pilot scale experiments to evaluate and demonstrate process conditions in Solvent Extraction operations.